

ColorWash 575 AT Zoom™

The ColorWash 575 AT Zoom includes all the features of the ColorWash 575 AT, and is enhanced with an extremely smooth linear motorized zoom that ranges from 8° to 50°. This is a great advantage, enabling the fixture a wider light output, making the ColorWash 575 AT Zoom suitable for all types of professional installations.



Spécifications Techniques

Source

- Lamp: Compact high-pressure metal halide lamp
- Base: GX9.5
- Approved model: Philips MSR 575/2
- Control: Automatic and remote on/off
- Ballast: Magnetic

Systeme optique

- High luminous-efficiency glass reflector
- Fresnel lenses of diameter 200 mm
- Internal diffusion lens of diameter 136 mm

Spécifications électriques et connectique

- Wiring options: EU model - 208/230/240V, 50/60Hz, US model - 100/120/208/230V, 50/60Hz
- Power consumption: 720VA at 230V/50Hz

Spécification mécanique

- Height: 588 mm (23.1") - head in horizontal position
- Width: 470 mm (18.5")
- Depth: 446 mm (17.6")
- Weight: EU model - 31 kg (68.3 lbs), US model - 34.5 kg (76.1 lbs)

Spécifications thermiques

- Maximum ambient temperature (Ta): 40°C (104°F)
- Maximum surface temperature: 80°C (176°F)

Contrôle et programmation

- Protocol: USITT DMX-512, RDM support
- Control channels: 16, 18, 19, 21
- DMX channels: 4 protocol modes
- Master/Slave operation
- Stand-alone operation
- 3-editable programs, each up to 99 steps
- Built-in demo sequences
- Display: 4-digit LED display
- Pan/Tilt resolution: 16bit
- Colour wheel positioning: 8 or 16bit
- Zoom: 8 or 16bit
- Dimmer: 8 or 16bit
- Movement control: Tracking and vector
- Built-in analyzer for easy fault finding
- Data in/out: Locking 3-pin & 5-pin XLR

Effets Électromécaniques

- Cyan: 0 - 100%
- Magenta: 0 - 100%
- Yellow: 0 - 100%
- CTO: 0 - 100%
- Colour wheel: 5 replaceable "SLOT&LOCK" colours + open
- Dimmer/Shutter: Full range dimming and variable strobe effect
- Zoom: 8° - 50°
- Pan: 530°
- Tilt: 28°

Accroche


- Mounting points: 4 pairs of ¼-turn locks
- 2x Omega bracket with ¼-turn quick locks

Accessoires optionnels

- Module of front wide-angle lens D200 (87° angle)
- Remote Control IR
- Top Hats

Gobos & Couleurs

Roue de couleurs




14070121



14070119



14070118



14070123



14070122