

# ColorSpot 250 AT™

The ColorSpot 250 AT includes a new rotating gobo wheel with 7 replaceable "SLOT&LOCK" dichroic glass gobos + open, and a new colour wheel hosting 10 replaceable "SLOT&LOCK" colours + open. The 3-facet rotating prism is now also replaceable. Completely new software enables very smooth rotations of gobos and prism, and 8 or 16-bit resolution for gobo indexing, prism indexing and dimmer. The improved cooling system ensures better operating conditions for lamp and reduces noise at the same time. The ColorSpot 250 AT is aimed at the TV studios, small and middle sized clubs and discotheques, and various types of installations.



# Spécifications Techniques

## Source

- Lamp: Compact high-pressure metal halide lamp
- Base: GY9.5
- Approved model: Philips MSD 250/2
- Control: Automatic and remote on/off
- Ballast: Magnetic

## Systeme optique

- Standard objective: 15°
- Optional objectives: 12° and 18°

## Effets Électromécaniques

- Colour wheel: 10 replaceable "SLOT&LOCK" dichroic filters + open
- Gobo wheel: 7 rotating, indexable, replaceable "SLOT&LOCK" glass gobos + open
- Interchangeable high-speed rotating 3-facet prism, optional frost filter supplied with the fixture
- Dimmer/Shutter: Full range dimming and variable strobe effect
- Focus: Motorized focus
- Pan: 530°
- Tilt: 280°

## Contrôle et programmation

- Protocol: USITT DMX-512, RDM support
- Control channels: 14, 16, 18 or 20
- DMX channels: 4 protocol modes
- Built-in demo sequences
- Display: 4-digit LED display
- Pan/Tilt resolution: 16bit
- Colour wheel: 8 or 16bit
- Gobo indexing: 8 or 16bit
- Focus: 8 or 16bit
- Dimmer: 8 or 16bit
- Master/Slave operation
- Stand-alone operation
- 3-editable programs, each up to 99 steps
- Movement control: Tracking and vector
- Built-in analyzer for easy fault finding
- Data in/out: Locking 3-pin XLR + 5-pin XLR

## Gobos rotatifs

- Dichroic glass gobos - outside diameter: 26.8 mm, image diameter: 22.0 mm, thickness: 1.1 mm, high temperature borofloat or better glass
- Glass gobo - outside diameter: 26.8 mm, max. thickness: 4 mm, high temperature borofloat or better glass

## Spécifications thermiques

- Maximum ambient temperature (Ta): 40 °C (104 °F)
- Maximum surface temperature: 80 °C (176 °F)

## Spécifications électriques et connectique

- Wiring options: EU model - 208/230/240 V, 50/60 Hz, US model - 100/120/208/230 V, 50/60 Hz
- Power consumption: 410 VA at 230 V/50 Hz

## Spécification mécanique

- Height: 483 mm (19.0") - head in horizontal position
- Width: 419 mm (16.5")
- Depth: 438 mm (17.3")
- Weight: EU model - 20.5 kg (45.2 lbs), US model - 23.5 kg (51.8 lbs)

**Accroche**

- Mounting points: 4 pairs of ¼-turn locks
- 2x Omega bracket with ¼-turn quick locks

**Accessoires optionnels**

- Objective 12°
- Lens-module 18°

## Gobos & Couleurs

### Roue de gobos rotatifs



15020141



15020140




15020139



15020138



15020137



15040011



15030016

### Roue de couleurs



14070069




14070067



14070060




14070066



14070062




14070063



14070064



14070065



14070007