

LEDBlinder 196 LT

The LEDBlinder 196 LT is the first entertainment based LED products. The unit is fitted into the industry standard 8-lite casing and offers set and lighting designers all the options.

LEDBlinder is a LED version of the popular 8-lite Molefay, a staple of the rock n roll world, featuring 8 LED modules, each with 12 RGB LEDs. Each four pairs of modules are separately controllable. This product is aimed at all stage lighting markets and television productions and for arenas and larger venues.



The LEDBlinder 196 LT is the first entertainment based LED products. The unit is fitted into the industry standard 8-lite casing and offers set and lighting designers all the options. LEDBlinder is a LED version of the popular 8-lite Molefay, a staple of the rock "n" roll world, featuring 8 LED modules, each with 12 RGB LEDs. Each four pairs of modules are separately controllable. This product is aimed at all stage lighting markets and television productions and for arenas and larger venues.

Spécifications Techniques

Source

- High-Power 1W Luxeon LEDs
- 32 Red LEDs, 32 Green LEDs, 32 Blue LEDs
- < 50.000 hrs Rated Life

Angle faisceau

- 25° beam angle of each LED

Frost, diffusion

- Optional frost filters (glass or film) for even light distribution

Couleurs

- 16,7 million colours (24 bit)
- Pre-programmed colours & rainbow effect
- Dynamic colour balance between white and red, green, blue colours during production
- White balance pre-programmed via LED control panel

Dimmer, Strobe

- Electronic dimmer for light output adjustment from 0 to 100%
- High speed white or full colour strobe, flash rate 1-25 fps

Spécification mécanique

- Height: 810 mm (31.9")
- Width: 480 mm (18.9")
- Depth: 190 mm (7.5")
- Weight: 18 kg (39.7 lbs)

Spécifications thermiques

- Maximum ambient temperature: 40°C (104°F)
- Maximum housing temperature: 60°C (140°F)

Contrôle et programmation

- Protocol: USITT DMX-512
- Control options: DMX, Auto-trigger
- Operation modes: Master/Slave, Stand-alone
- Programs: 6 built-in programs + 3 user editable programs up to 30 steps each
- Display: 4 digit LED
- Manual control of all DMX channels via LED control panel
- 4 pairs of LED modules

Canaux DMX

- Mode 1: 15 channels
- Mode 2: 12 channels
- Mode 3: 6 channels
- Mode 4: 3 channels

Connexion

- Control: DMX 512
- DMX connection: 3-pin or 5-pin XLR-sockets

Consommation électrique

- Input Voltage: 100-240 V, 50/60 Hz
- Fuse: T 3.15 A
- Max. Power Consumption: 140 VA

Accessoires optionnels

- Set glass frost
- Set film frost
- Cover for LEDBlinder 196 LT