

iParFect 150™ FWQ RGBW

The all-new iParFect 150 FWQ RGBW is loaded with killer features. It has an exceptionally-wide zoom range, is completely silent with passive cooling and with an IP 65 rating, is ideal for television, theatres, concert halls and any kind of outdoor events.

**Source**

7x 40W RGBW multichips

**Flux lumineux**

2.090 lm, 6.800 lx @ 5m

**Plage de Zoom**

3,8° - 60°



Other characteristics include CMY & RGBW colour control, 18-bit dimming and Tungsten emulation with both selectable & variable colour temperatures providing total output control.

The powerful, punchy beam with a zoom range of 3,8° to 60°, combined with a Fresnel style beam edge, results in a smooth, homogenised beam of light.

Now equipped with Robe's innovative lens coating technology which brings benefits such as bright and clear lenses, no scratches or marks, higher light output and longer intervals between cleaning.

Spécifications Techniques

Source

- Light source type: 7x 40W RGBW multichips
- LED life expectancy: min. 50.000 hours
- Typical lumen maintenance: L70/B50 @ 50.000 hours

Système optique

- Robe's proprietary optical design
- High-efficiency zoom optical system, ratio 15,5:1
- Zoom range: 3.8° - 60°
- Diffusion filter imbedded
- Fixture total lumen output:
 - 2.090 lm (integrating sphere)
 - 1.676 lm (goniophotometer)
- Illuminance: 6.800 lx @ 5 m
- RLCT™ Innovative lens coating technology (Patent pending)

Effets et fonctions dynamiques

- Colour mixing mode RGBW or CMY
- Variable CTO: 2.700K - 8.000K
- Virtual Colour Wheel: with 66 preset swatches
- Tungsten lamp effect at whites: 2.700K and 3.200K (red shift and thermal delay)
- Motorized exceptionally quiet zoom
- Pre-programmed random strobe & pulse effects
- High resolution electronic dimming: 0 - 100%
- L3™ - (Low Light Linearity) Imperceptible 18 bit dimming for ultra smooth fade to black

Contrôle et programmation

- Setting & Addressing: two-row LCD display & 4 control buttons, stand-alone operation with 3 editable programs (each up to 25 steps)
- Protocols: USITT DMX-512, RDM
- Wireless CRMX™ technology from Lumen Radio - on request
- DMX Protocol modes: 2
- Control channels: 17, 11
- RGBW / CMY: 8 or 16 bit
- Zoom: 8 or 16 bit
- Dimmer: 8 or 16 bit (internal 18 bit)

Spécifications thermiques

- Maximum ambient temperature: 40°C (104°F)
- Maximum surface temperature: 80°C (176°F)
- Minimum operating temperature: -10°C (14°F)

Spécifications électriques et connectique

- Power supply: Electronic auto-ranging
- Input voltage range: 100-277 V, 50/60 Hz
- Power consumption: Max. 220 W
- Power connector in/out: IP 65 Neutrik powerCON TRUE1 in/out
- DMX and RDM data in/out: Locking 5-pin XLR

Certifications

- CE Compliant
- cETLus Compliant

Spécification mécanique

- Height: 234.7 mm (9.24")
- Width: 251 mm (9.88")
- Depth: 413 mm (16.26") without hanging bracket / 489.4 mm (19.27") with hanging bracket
- Weight: 7.3 kg (16.1 lbs)
- Ingress protection rating: IP65

Accroche

- Mounting horizontally or vertically via mounting yoke
- Universal operating position
- Safety cable attachment point

Éléments inclus

- User Manual

Accessoires optionnels

- Gel frame: 10980372
- Barndoor module: 10980349
- Outdoor barndoor module: 10980884
- Doughty Trigger Clamp: 17030386
- Safety wire 36 kg: 99011963
- Mains Cable powerCON TRUE1 In/open ended, 2m EU, Extérieur : 13052276-01
- Mains Cable powerCON TRUE1 In/open ended, 2m US, Extérieur : 13052277-01
- Single Top Loader Case: 10120238
- Six Pack Top Loader Case: 10120239
- Eight Pack Top Loader Case: 10120240
- Dual Foam Shell: 20020329

Légal

- iParFect 150™ is a Trademark of Robe lighting s. r. o.
- iParFect 150™ FWQ RGBA is patented by Robe lighting s. r. o. and is protected by one or more pending or issued patents