

iPointe®

OUR OUTDOOR POINT!

**Source**

Osram Sirius HRI 310 W RO

**Flux lumineux**

Bright output of 1.584.660 lx @ 5 m

**Plage de Zoom**

1.8°- 21° beam mode, 3°- 42° spot mode

**Effets**CMY mixing, rotating and static gobo wheel,
animation wheel, 12 beam and flower effects

Robe's iPointe combines innovative ingress protection with the spectacular effect features of the MegaPointe - the best product on the market in its category.

Perfect for festivals, concerts and outdoor events and any scenario needing to deal with inclement or unpredictable weather - the iPointe is a bright, powerful multifunctional luminaire that works equally well as a beam, spot, effect and wash fixture.

The ingenious ingress protection has been designed and developed diligently over two years by Robe's R'n'D team and comprises a series of interconnected filters and air chambers that prevent water from entering the fixture as well as the need for frequent cleaning and maintenance.

The iPointe's impressive lightsource is a 310W lamp, with a lifetime of up to 4.000 hours, specially developed for Robe by Osram. It produces a brilliant, crystal clear, razor-edged beam, adjustable from a tight, punchy 1.8 degree beam to a wide 42 degrees spot.

The beam can be accurately shaped and positioned by using the innovative framing shutters emulation.

Both static and rotating glass gobos produce precision in-air effects and projected images with a sharp, high-contrast, flat field. An inventive new effects engine can produce 12 varying beam and 'flower' effects, all of this taking a winning combination of creativity and weather-resistance to new levels.

Thanks to its design, the iPointe offers seamless cross-usage with MegaPointe, featuring the same DMX control, but in well-protected, water resistant housing.

Pointe, MegaPointe, iPointe. The best all-in-one product range!

Spécifications Techniques

Source

- Lamp: Discharge short arc lamp with integrated reflector
- Approved model: Osram Sirius HRI 310W RO
- Lifetime:
 - 2.500 hours @ 310W Standard mode
 - 3.500 hours @ 230W Eco mode
 - 4.000 hours @ LL mode with auto recovery
- CRI: 80/90
- CCT:
 - Light output 7.200K
 - Lamp 8.500K
- Control: Automatic and remote on/off
- Ballast: Electronic
-

Systeme optique

- Robe's proprietary optical design (Patent pending)
- Zoom optical system: 14:1
- Zoom range:
 - 1.8° - 21° beam mode
 - 3° - 42° spot mode
- Output lens diameter: 150 mm
- Fixture total lumen output: 11.628 lm
- Light output:
 - Beam mode
 - 1.8°: 1.584.660 lx @ 5 m
 - 1.8°: 99.040 lx @ 20 m
 - Spot mode
 - 3°: 381.540 lx @ 5 m
 - 3°: 23.846 lx @ 20 m
-

Effets et fonctions dynamiques

- Cyan: 0 - 100%
- Magenta: 0 - 100%
- Yellow: 0 - 100%
- Colour Wheel: 13 dichroic filters + white
- Rotating gobo wheel: 9 rotating gobos + open, indexable and replaceable gobos
- Static gobo wheel: 14 gobos + open
- Animation wheel: Aluminium animation wheel, used alone or in combination with gobos, rotating in both directions at variable speed
- Innovative Effect Engine consisting of 6 prisms placed on two wheels, producing 12 various Beam and Flower effects
- Beam shaper emulating framing shutters and creating rectangular beam shapes, rotatable and indexable (Patented)
- Frost: variable 1° (light) and 5° (medium)
- Motorized zoom and focus
- Remote Hot-spot control: adjustable from 5:1 to 2.5:1 in spot mode and from 7:1 to 2.7:1 in beam mode
- Pre-programmed random strobe & pulse effects
- Dimmer: 0 - 100%
-

Contrôle et programmation

- Setting & Addressing: ROBE Navigation System 2 (RNS2)
- Display: QVGA Robe screen with battery backup, gravitation sensor for auto screen positioning, operation memory service log with RTC, built-in analyser for easy fault finding, NFC app controller
- Protocols: USITT DMX-512, RDM, ArtNet, MA Net, MA Net2, sACN
- REAP™ - Robe Ethernet Access Portal
- Wireless CRMX™ technology from Lumen Radio: standard
- DMX Protocol modes: 2
- Control channels: 39,34
- Pan/Tilt resolution: 16 bit
- Colour wheel positioning: 8 or 16 bit
- CMY: 8 bit
- CRI Selection: 80 or 90
- Rotating gobo wheel positioning: 8 bit
- Gobo indexing & rotation: 8 or 16 bit
- Static gobo wheel positioning: 8 bit
- Animation wheel: 8 bit
- Animation wheel rotation: 8 or 16 bit
- Prism indexing & rotation: 8 bit
- Frost: 8 bit
- Zoom: 8 or 16 bit
- Focus: 8 or 16 bit
- Hot-Spot: 8 bit
- Dimmer: 8 or 16 bit
-

Mouvement

- Pan movement: 540°
- Tilt movement: 265°
- Movement control: Standard and Speed
- Automatic Pan/Tilt position correction
- EMS™: Electronic Motion Stabilizer system for Pan & Tilt reducing beam deviation caused by truss movement or vibration (Patented)
-

Gobos rotatifs

- Glass gobos: 9 rotating gobos + open
- Outside diameter: 15.9 mm
- Image diameter: 12.5 mm
- Thickness: 1.1 mm
- High temperature borofloat or better glass
- "SLOT&LOCK" system for easy replacement of gobos
-

Gobos statiques

- Aluminium wheel with fixed gobos: 10 gobos & 4 beam reducers + open position
-

Spécifications thermiques

- Maximum ambient temperature: 35°C (95°F)
- Maximum surface temperature: 90°C (194°F)
- Minimum operating temperature: -10°C (14°F)
-

Spécifications électriques et connectique

- Power supply: Electronic auto-ranging
- Input voltage range: 100-240 V, 50/60 Hz
- Power consumption: max. 550 W
- Power in connector: IP65 Neutrik powerCON TRUE1
- DMX and RDM data in/out: IP65 Locking 3-pin & 5-pin XLR connectors
- Ethernet port in: IP65 RJ45 connector
-

Spécification mécanique

- Height: 761 mm (30.0") - head in vertical position
- Width: 506 mm (19.9")
- Depth: 277 mm (10.9")
- Weight: 38 kg (83.8 lbs)
- Ingress protection rating: IP55
-

Accroche

- Mounting positions: Horizontally or vertically
- Universal operating position
- Mounting points: 2 pairs of 1/4-turn locking points
- 2x Omega adaptors with 1/4-turn quick locks
- Pan and Tilt transport locks
- Safety cable attachment point
-

Éléments inclus

- User Manual
- Omega Adaptor CL-regular 2 pcs
- Power cord including powerCON TRUE1 In connector
-

Accessoires optionnels

- Lamp Osram Sirius HRI 310W RO: 14080065
- Doughty Trigger Clamp: 17030386
- Safety wire 50 kg: 99011957
- Single Top Loader Case: 10120249
- Dual Top Loader Case: 10120251
- Foam Shell: 20020350
-

Légal

- iPointe® is Registered Trademark of Robe lighting s. r. o.
- iPointe® is patented by Robe lighting s. r. o. and is protected by one or more pending or issued patents
-

Certifications

Gobos & Couleurs

Roue de gobos rotatifs



15020341



15020352



15020351



15020347



15020337



15020350



15020355




15020354




15020342


Roue de couleurs



14070445




14070446




14070447




14070448




14070449




14070450




14070451




14070452




14070453




14070454



14070455




14070456



14070457

Roue de gobos fixes




99015494-1



99015494-2



99015494-3




99015494-4




99015494-5



99015494-6




99015494-7



99015494-8




99015494-9



99015494-10

Roue d'animation


11020239

Roue de prismes 1


14050031




14050033




14050030

Roue de prismes 2

14050031



14050032



14050034