

# LEDWash 600X™

The super-slim LEDWash 600X features a new generation of 30% brighter 37 x 15 Watt RGBW multichip LEDs with colour output ranging from gentle pastels to the richest saturation.

**Source**

37x 15 W RGBW LED multichips

**Flux lumineux**

8.990 lm, 9.780 lx @ 5 m

**Plage de Zoom**

8° - 63°

**Effets**

3 LED rings control, rainbow effects, tungsten lamp effect, pre-programmed whites



Arranged in 3 concentric rings these LEDs offer unique possibilities for creating stunning colour and pattern audience blinding effects as well as for providing comprehensive and perfectly even wash coverage.

This system sets the LEDWash 600X ahead of any other LED wash light products, making it a truly „multi-purpose“ unit, equipped also with Robe’s patented an extremely versatile 8-63 degree motorised zoom, powerful fast strobing and pre-programmed pulse strobe effects.

PowerCON True1 chassis connector has been now added on the back of the fixture’s base to guarantee a safe power connection. The powerCON TRUE1 connector can be connected or disconnected under load or live.

# Spécifications Techniques

## Source

- Light source type: 37x 15W RGBW LED multichips
- LED life expectancy: min. 60.000 hours
- Typical lumen maintenance: 70% @ 60.000 hours

## Système optique

- Robe's proprietary optical design
- High - efficiency zoom optical system, ratio 8:1
- Zoom range: 8° - 63°
- Fixture total lumen output:
  - 8.990 lm (integrating sphere)
  - 7.218 lm (goniophotometer)
- Brightness: 9.780 lx @ 5 m

## Effets et fonctions dynamiques

- Colour mixing mode RGBW
- 4 individually controllable LED rings
- Virtual Colour Wheel: 237 colours including whites (2.700K, 3.200K, 4.200K, 5.600K and 8.000K)
- Tungsten lamp effect at whites: 2.700K and 3.200K (red shift and thermal delay)
- Colour rainbow effect with variable speed
- Pre-programmed random strobe & pulse effects
- Electronic strobe effect with variable speed up to 20 Hz
- High resolution electronic dimming: 0 - 100%

## Contrôle et programmation

- Setting & Addressing: ROBE Navigation System 2 (RNS2)
- Display: QVGA Robe touch screen with battery backup, gravitation sensor for auto screen positioning, operation memory service log with RTC, stand-alone operation with 3 editable programs (each up to 100 steps), built-in analyser for easy fault finding
- Protocols: USITT DMX-512, RDM, ArtNet, MA Net, MA Net2
- Wireless CRMX™ technology from Lumen Radio: On request
- DMX Protocol modes: 6
- Control channels: 37, 21, 15, 10, 37, 24
- Pan/Tilt resolution: 16 bit
- RGBW: 8 or 16 bit
- Zoom: 8 bit
- Dimmer: 8 or 16 bit

## Mouvement

- Pan movement: 450°
- Tilt movement: 300°
- Automatic Pan/Tilt position correction

## Spécifications thermiques

- Maximum ambient temperature: 45°C (113°F)
- Maximum surface temperature: 75°C (167°F)
- Minimum operating temperature: -5°C (23°F)

## Spécifications électriques et connectique

- Power supply: Electronic auto-ranging Input voltage range: 100-240 V, 50/60 Hz
- Power consumption: Max. 415 W at 230 V / 50 Hz
- Power in connector: Neutrik powerCON TRUE1
- DMX and RDM data in/out: Locking 3-pin & 5-pin XLR
- Ethernet port in: RJ45

## Certifications

- CE Compliant
- cETLus Compliant

## Spécification mécanique

- Height: 444 mm (17.5")
- Width: 343 mm (13.5")
- Depth: 203 mm (8")
- Weight: 10.6 kg (23.4 lbs)
- Ingress protection rating: IP20

## Accroche

- Mounting positions: Horizontally or vertically
- Universal operating position

## Éléments inclus

- User Manual
- Omega Adaptor CL-regular 2 pcs
- Power cord including powerCON TRUE1 In connector

## Accessoires optionnels

- Transparent EggCrate: 10980114
- Top hat: 10980101
- Mounting adapter for one omega holder: 10980100
- Doughty Trigger Clamp: 17030386
- Safety wire 35 kg: 99011963
- Single Top Loader Case: 10120097-01
- Dual Top Loader Case: 10120103-01
- Quad Top Loader Case: 10120102-01
- Six Pack Top Loader Case: 10120104-01
- Foam Shell: 20020197

## Légal

- LEDWash 600X™ is a Trademark of Robe lighting s. r. o.
- LEDWash 600X™ is patented by Robe lighting s. r. o. and is protected by one or more pending or issued patents