

FOG 1000 FT™

FOG 1000 FT™, is designed for special purposes and applications for which no other fog machines are available. It uses mirror-piping heater technology that supports advance features and high-throughput burst mode, with extreme low energy consumption. This unique design offers great versatility, and the machine can be mounted either on the ground with the output directed upwards to create a column effect, or can be wall mounted for easy blending in with the surroundings. It can also be used in the upright position via the carrying handle just like any standard fog machine. Onboard DMX or inbuilt electronic low fluid detector are amongst another features. Lightweight, sleek and compact design, easy installation and maintenance. FOG 1000 FT™ is perfect for theatrical and studio applications, large halls and spaces, concerts and touring, DJ events and clubs.



Spécifications Techniques

Description

- Power: AC 230 V/AC 240 V, 50 Hz or AC 100 V/AC 120 V/60 Hz optionally
- Heater: 1,000 W
- Output: 10,000 cu.ft/min.
- Fluid Consumption Rate: 11 min/l (100% Output)
- First Heat-up Time: 10 min.
- Tank Capacity: 2.4 liters
- Remote Included: Fogging Switch: ON/OFF
- Weight: 9.8 kg
- Dimensions (mm): L 370 x W 295 x H 135
- Liquid Used: Standard Fog/Performance Fog/Premium Fog